

# ELFTEX® P100 SPECIALTY CARBON BLACK

### Product highlights

ELFTEX® P100 specialty carbon black is a p-type carbon black suitable for use in pressure pipe applications, particularly those that follow ISO4427 and ISO4437 standards that specify maximum particle size, sulfur content and dispersion requirements. P-type carbon blacks are specialty blacks with narrow product specifications for applications requiring exceptional UV performance and excellent physical and chemical cleanliness.

### Key applications

ELFTEX P100 specialty carbon black is especially suited for use in plastic products requiring excellent UV protection. Key applications include:

- ◆ Pressure pipe for potable water and gas
- ◆ Irrigation pipe
- ◆ Utility pipe
- ◆ Geomembranes

### Performance features

ELFTEX P100 specialty carbon black enables low moisture absorption in the compound and its morphology delivers good processability due to lower viscosity, enabling smooth surfaces in end products. In summary, ELFTEX P100 specialty carbon black has:

- ◆ Low sulfur and toluene
- ◆ Low grit and ash
- ◆ Particle size less than 25 nm
- ◆ Excellent UV performance

For end products, it:

- ◆ Enables low compound moisture absorption
- ◆ Enables higher MFI than other p-type carbon blacks for superior processability



# ELFTEX® P100 SPECIALTY CARBON BLACK

## TYPICAL PROPERTIES

PROPERTY	DATA	TEST METHOD
Iodine number (mg/g)	79	ASTM D-1510
OAN (cc/100g)	104	ASTM D-2414
Moisture as packed (%)	<1.0	ASTM D-1509
325 mesh residue (ppm)	<20	ASTM D-1514
Ash (%)	<0.1	ASTM D-1506
Total sulfur (%)	<0.1	ASTM D-1619
Particle size (nm)	<25	ASTM D-3849
Toluene extract (%)	<0.03	ASTM D-4527

### Product form and logistics

- ◆ Product Form: pellets
- ◆ Regional availability: global
- ◆ Bag Packaging Options: 20 kg bags
- ◆ Bulk Packaging Options: 500 kg FIBC

For information on product-specific storage conditions, please refer to the applicable Safety Data Sheet (SDS) available from your Cabot representative or at [cabotcorp.com](http://cabotcorp.com).

The ELFTEX name is a registered trademark of Cabot Corporation.

**NORTH AMERICA**  
Business & Technology Center  
157 Concord Road  
Billerica, MA 01821-7001  
United States  
T +1 800 462 2313  
F +1 978 670 7035

**SOUTH AMERICA**  
Cabot Brasil Industria e  
Comercio Ltda.  
Rua do Paraíso 148 - 5º andar  
04103-000 São Paulo  
Brazil  
T +55 11 2144 6400  
F +55 11 3253 0051

**EUROPE**  
SIA Cabot Latvia  
101 Mukusalas Street  
LV-1004 Riga  
Latvia  
T +371 670 50 900  
F +371 670 50 985

**MIDDLE EAST/AFRICA**  
Cabot Specialty Chemicals  
Jebel Ali Free Zone  
LOB 15, Office 424, Dubai  
United Arab Emirates  
T +971 4 8871 800  
F +971 4 8871 801

**ASIA PACIFIC**  
Cabot China Ltd.  
558 Shuangbai Road  
Minghang District  
Shanghai 201108  
China  
T +86 21 5175 8800  
F +86 21 6434 5532

**JAPAN**  
Cabot Specialty Chemicals, Inc.  
Sumitomo Chiba-Daimon Bldg. 3F  
2-5-5 Shiba Daimon,  
Minato-ku, Tokyo 105-0012  
Japan  
T +81 6820 0255  
F +81 3 5425 4500

The data and conclusions contained herein are based on work believed to be reliable, however, Cabot cannot and does not guarantee that similar results and/or conclusions will be obtained by others. This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and CABOT DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AS TO (i) SUCH INFORMATION, (ii) ANY PRODUCT OR (iii) INTELLECTUAL PROPERTY INFRINGEMENT. In no event is Cabot responsible for, and Cabot does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.